

Docker

```
docker ps -a
docker run -it -rm <container> bash
whoami
exit
```

Command	Description
run <image>[:tag] [command]	run container/image
Basic	
-it	–interactive and –tty
–rm	remove container
-d	run in background
-v [host-folder]:[container-folder]	add volume
stop <name/id>	
Extended	
–name [name]	define container name
-e <env>, –env-file <env-file>	add env
-h <hostname>	set hostname
-m <memory>	set memory limit
–network,=none	disable network
stop \$(docker ps -a -q)	stop all containers
docker rm \$(docker ps -a -q)	rm all containers
volume rm \$(docker volume ls -q)	rm all images
Compose	
compose up	down [-d]
Others	
search <searchword>	search registry
search -f is-official=true <sw>	
search -f stars=100 <sw>	

Docker commit

```
docker commit [OPTIONS] CONTAINER_ID_OR_NAME [REPOSITORY[:TAG]]
```

-m "message"	Commit message
-a "author"	Author name
-c: <instructions>	Applies Dockerfile instructions
workflow	
docker ps -a	
docker commit -m "did something" <current_container> <custom_image:v#>	

Network

<code>docker network create <name></code>	
<code>docker run -itd --network=<name> <image></code>	
<code>docker network create --subnet 10.0.2.0/24 <name></code>	
<code>docker run -itd --network=<name> --ip=10.0.0.69 <image></code>	