

Velociraptor

<https://docs.velociraptor.app/docs/deployment/quickstart/>

Basic workflow

```
docker image load -i ./ir-velociraptor.tar
vim config/server.config.yaml
# add server ip
docker compose up

docker exec -it ir-velociraptor /opt/velociraptor/linux/velociraptor --
config ./config/server.config.yaml user add admin --role administrator

#velociraptor config client --org="root" --config
/velociraptor/config/server.config.yaml
docker exec -it ir-velociraptor /opt/velociraptor/linux/velociraptor config
client --org="root" --config /velociraptor/config/server.config.yaml >
client.config.yaml

#test
./velociraptor --config client.config.yaml client -v
velociraptor.exe --config client.config.yaml client -v
```

```
sed -i -E 's|(- https://)[0-9.]+(:[0-9]+)/|\1<ip>\2|' data/config.yaml
```

How it works:

-E: Enables extended regular expressions (so we can use groups like ()).

(- https://): Group 1 (\1), matches the prefix.

[0-9.]+: Matches any combination of numbers and periods (the IP address).

(:[0-9]+)/: Group 2 (\2), matches the port and trailing slash (e.g., :20000/).

\1192.168.1.50\2: Rebuilds the line using the original prefix, your new IP, and the original port.